



PRODUCT DATASHEET

SPC BRAKE FLUID DOT 4

Brake Fluid

SPC BRAKE FLUID DOT 4 is a premium quality brake and clutch fluid, blended from superior material to a high standard of purity and boiling point.

PERFORMANCE STANDARDS

SPC BRAKE FLUID DOT 4 meets the following requirements:

- SAE J1703
- FMVSS 116 DOT 4
- ISO 4925
- VV-B-680 B
- JIS K 2233 Class 4

BENEFITS

SPC BRAKE FLUID DOT 4 provides the following benefits:

- Provides good braking performance under wide temperature range.
- Maintains high boiling point to ensure absolute safety under high temperature operation.
- Exhibits good chemical stability to ensure long fluid service life.
- Prevents fluid loss due to compatibility of rubber seals.
- Provides good lubricating and antiwear properties.

APPLICATIONS

SPC BRAKE FLUID DOT 4 is suitable for use in normal motor vehicles and motorcycles of both drum and disc types hydraulic brake and clutch systems. It mixes safely with other SAE J1703, DOT 3 and DOT 4 brake fluid.

TYPICAL CHARACTERISTICS

SPC BRAKE FLUID DOT 4

Equilibrium Reflex Boiling Point	
– Wet, deg C	157
Viscosity, Kinematic	
at -40 deg C, cSt	1205
at 100 deg C, cSt	1.5 min
pH Value	7.5

The above figures are typical of current production and do not constitute a specification. Minor variations may occur.