



# PRODUCT DATASHEET

## SPC GEARLUBE OG / OG FLUID

Open Gear Lubricant

---

**SPC GEARLUBE OG / OG FLUID** are a black adhesive and cohesive open gear and wire rope lubricants. It is formulated to provide improve water resistance, water displacement and antirust properties.

### BENEFITS

**SPC GEARLUBE OG / OG FLUID** provide the following benefits:

- Protection against shock load.
- Resistance against throw-off.
- Durable lubricating films.
- Protection against rusting.

### APPLICATIONS

**SPC GEARLUBE OG** is recommended for lubrication of open gears, chains and wire ropes.

The **GEARLUBE OG FLUID** contains a diluent to facilitate application and where preheating before application is not practical.

Another lower viscosity grade that is half of the OG Fluid viscosity, **GEARLUBE OG FLUID M**, is also available.

## TYPICAL CHARACTERISTICS

---

### SPC GEARLUBE OG / OG FLUID

---

Grade	OG	OG Fluid M	OG Fluid
Viscosity, Kinematic			
at 50 <sup>0</sup> C, cSt	—	820	1700
at 100 <sup>0</sup> C, cSt	1015	420	985
Timken OK Load, kg	22	18	20

---

04 July 2008

GEARLUBE OG & OG FLUID.doc

All the information contained in this document is considered to be accurate as of the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy of the data and information in this publication. It is the user's obligations to evaluate and use the products safely and to comply with all applicable laws and regulations. For more information, please contact your sales representative.