



# PRODUCT DATASHEET

## SPC ATF III

### Automotive Transmission Fluid

---

**SPC ATF III** is a high performance, multipurpose automatic transmission fluid for modern passenger cars and light trucks.

### PERFORMANCE STANDARDS

**SPC ATF III** meets the following performance requirements:

- Dexron III (H)
- Ford MERCON
- Allison C-4
- Caterpillar TO-2

### BENEFITS

**SPC ATF III** provides the following benefits:

- Provides excellent oxidation stability and deposit control under very high temperature and severe operating conditions.
- Exhibits excellent antiwear properties.
- Provides good antifoam properties.
- Maintains good antirust and anticorrosion properties.
- Provides minimum evaporation loss due to low volatility of the fluid.
- Exhibits excellent compatibility with synthetic rubber seals.

## APPLICATIONS

**SPC ATF III** is recommended for filling and topping-up of automatic and manual transmissions, transaxles and power steering systems meeting Dexron III, Dexron IIE, Dexron IID and Mercon specifications.

It is also recommended for on-highway and off-highway use in Allison heavy duty automatic transmissions.

## TYPICAL CHARACTERISTICS

---

### SPC ATF III

---

Viscosity, Kinematic	
at 40 deg C, cSt	37.9
at 100 deg C, cSt	7.6
Viscosity Index	176
Specific Gravity, 15.6 deg C	0.856
Flash Point, COC, deg C	187
Pour Point, deg C	-45

---

The above figures are typical of current production and do not constitute a specification. Minor variations may occur.